

What is claimed is:

1. A method for forming a silica-containing boule comprising the steps of:
  - (a) providing a substantially planar surface;
  - (b) providing a soot-producing burner having a burner face that comprises first, second, third, fourth, fifth, and sixth gas-emitting regions, the second region surrounding the first region, the third region surrounding the second region, the fourth region surrounding the third region, the fifth region surrounding the fourth region, and the sixth region surrounding the fifth region;
  - (c) providing a mixture comprising an inert gas and a halide-free, silicon-containing material to the first region;
  - (d) providing oxygen to the second region;
  - (e) providing a mixture of a combustible gas and oxygen to the third region;
  - (f) providing a mixture of a combustible gas and oxygen to the fourth region;
  - (g) providing a mixture of a combustible gas and oxygen to the fifth region;
  - (h) providing oxygen to the sixth region; and
  - (i) collecting silica-containing soot on the substantially planar surface to form the boule.
2. The method of Claim 1 wherein the burner produces a stream of soot particles and the width of the stream of soot particles is controlled to enhance the efficiency of step (i).
3. The method of Claim 2 wherein the width of the stream of soot particles is reduced to enhance the efficiency of step (i).
4. The method of Claim 2 wherein the width of the stream of soot particles is controlled by controlling the amount of oxygen provided to the sixth region.

5. The method of Claim 1 wherein the mixture of a combustible

6. The method of Claim 5 wherein the mixture of a combustible

7. The method of Claim 1 wherein the third, fourth, fifth, and

8. The method of Claim 1 wherein the boule has a thickness

9. The method of Claim 1 wherein the silica-containing soot is

10. A method for forming a silica-containing boule comprising:

(a) providing a furnace which comprises:

(i) a cavity;

(ii) at least one burner which produces a stream of soot

particles; and

- (iii) a substantially planar surface within the cavity for

(b) providing a halide-free, silicon-containing material to the at

(c) collecting the soot particles produced by the at least one

wherein the width of the stream of soot particles is controlled to

11. The method of Claim 10 wherein the width of the stream of

12. The method of Claim 10 wherein the at least one burner has a

13. The method of Claim 12 wherein the width of the stream of soot particles is less than 12 millimeters at a distance of 150 millimeters from said face.

14. The method of Claim 10 wherein the at least one burner has a burner face and the width of the stream of soot particles is less than 25 millimeters at a distance of 200 millimeters from said face.

15. The method of Claim 14 wherein the width of the stream of soot particles is less than 12 millimeters at a distance of 200 millimeters from said face.

16. The method of Claim 10 wherein the boule has a thickness greater than six inches.

17. The method of Claim 10 wherein the soot particles are consolidated as they are collected in step (c).

18. A soot-producing burner comprising a burner face which comprises first, second, third, fourth, fifth, and sixth gas-emitting regions, the second region surrounding the first region, the third region surrounding the second region, the fourth region surrounding the third region, the fifth region surrounding the fourth region, and the sixth region surrounding the fifth region, wherein:

- (a) the first region emits a mixture of a halide-free, silicon-containing material and an inert gas;
- (b) the second region emits oxygen;
- (c) the third region emits a mixture of a combustible gas and oxygen;
- (d) the fourth region emits a mixture of a combustible gas and oxygen;
- (e) the fifth region emits a mixture of a combustible gas and oxygen; and
- (f) the sixth region emits oxygen.

For 2000-06-23-00

20. The burner of Claim 18 wherein the burner comprises a baffle and the mixture of a combustible gas and oxygen emitted by the third region passes through the baffle before being emitted from the face of the burner.

22. Apparatus for producing silica-containing soot comprising:

- (a) a source of a mixture of a combustible gas and oxygen;
- (b) a burner for producing silica-containing soot; and
- (c) a source-to-burner conduit for carrying the mixture of a combustible gas and oxygen from the source to the burner;

(i) a burner face which comprises three concentric gas-emitting regions, each of which emits the mixture of a combustible gas and oxygen;

- (iii) a baffle between the source-to-burner conduit and the three gas-carrying conduits.